



A P P R O V A L S ®

Certificate of Conformity/Approval

Certificate No.: SAA-241277-EA

Certificate Holder: Shenzhen Boxinqi Technology Co.,Ltd
206 Block 2B, Dacheng Industry Zone,
Jihua Road, Longgang District,
Shenzhen 518112
P.R. China

Regulatory Definition: Power Supply or Charger

Product Description: LED Driver

Standard/s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: To be used with LED lighting only.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA-241277-EA (In accordance with NSW legislative requirements)

Initial Issue Date: 3 September 2024

Expiry Date: 3 September 2029

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277
Page 1 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-075FNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100FNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.17A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150FNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-200FNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 8.34A Suitable load range: 200W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-240FNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 10A Suitable load range: 240W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075TNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100TNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.17A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 2 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-150TNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-200TNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 8.34A Suitable load range: 200W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-240TNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 10A Suitable load range: 240W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075ANAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100ANAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.17A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150ANAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-200ANAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 8.34A Suitable load range: 200W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-240ANAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 10A Suitable load range: 240W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 3 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-075DNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100DNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.17A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150DNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-200DNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 8.34A Suitable load range: 200W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-240DNAV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 10A Suitable load range: 240W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-020FNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.84A Suitable load range: 20W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030FNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-040FNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.67A Suitable load range: 40W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 4 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-060FNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075FNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-020TNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.84A Suitable load range: 20W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030TNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-040TNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.67A Suitable load range: 40W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060TNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075TNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-020ANPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.84A Suitable load range: 20W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 5 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-030ANPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-040ANPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.67A Suitable load range: 40W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060ANPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075ANPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C
BQ-020DNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.84A Suitable load range: 20W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030DNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-040DNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.67A Suitable load range: 40W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060DNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 6 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-075DNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-006LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.25A Suitable load range: 6W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-009LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.37A Suitable load range: 9W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-012LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.5A Suitable load range: 12W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-018LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 0.75A Suitable load range: 18W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-024LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.0A Suitable load range: 24W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-036LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.5A Suitable load range: 36W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 7 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-048LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.0A Suitable load range: 48W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-075LNPV	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 3.125A Suitable load range: 75W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030FNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-036FNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.5A Suitable load range: 36W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060FNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100FNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.16A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150FNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 8 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-030TNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-036TNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.5A Suitable load range: 36W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060TNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100TNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.16A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150TNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030ANPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-036ANPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.5A Suitable load range: 36W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060ANPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Nill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 9 of 10



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating / Marking
BQ-100ANPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.16A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150ANPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-030DNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.25A Suitable load range: 30W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-036DNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 1.5A Suitable load range: 36W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-060DNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 2.5A Suitable load range: 60W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-100DNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 4.16A Suitable load range: 100W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover
BQ-150DNPV-SL	boqi	Input: 220-240V~ 50/60Hz Output: 24Vdc 6.25A Suitable load range: 150W ta:45°C, tc:80°C, Class I, IP20, Do-Not-Cover

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 03-09-24 241277

Page 10 of 10